

## Specifications - Engineered Strand Bamboo Collection

<b>Products:</b>			
Carbonized (FRE-OS14-142C)	* Coconut (FRE-OS15-189-CO)	<b>All products listed are FSC certified.</b>	
Natural (FRE-OS14-142N)	* Husk (FRE-OS15-189-Husk)		
Island (FRE-OS14-142ISL)	* Java (FRE-OS15-189-Java)		
	* Seashell (FRE-OS15-189-Sea)		
<b>Dimension &amp; Structure:</b>			
	Product size	14 x 142 x 1850mm (9/16" x 5 5/8" x RL to 72 7/8") *14 x 189 x 1850mm (5/8" x 7 7/16" x RL to 72 7/8")	
	Product Type	Engineered 3-Ply construction Tongue and Groove, End matched	
	Face Layer Thickness	3mm (1/8")	
	3-Layer Platform	11mm (7/16")	
	Face Layer Type	Smooth Face Brushed / Bleed for Island only	
	Edge Preparation	0.25mm micro-bevel	
<b>Species:</b>			
	Face Layer Species	Strand Bamboo	
	3-Layer Platform	Poplar	
	Moisture Content	6-8%	
<b>Adhesive/Finish:</b>			
	Adhesive	CARB Phase 2 Compliant	
	Coating Type	U.V. cured water based polyurethane	
	Surface Type	Closed pores	
	Glossiness Factor	40 ± 5 semi-gloss finish	
<b>Packaging:</b>			
	Square Feet per Carton	22.59 sq. ft(2.10 m <sup>2</sup> ) *30.07 sq. ft(2.80 m <sup>2</sup> )	
	Carton s per Pallet	48 * 40	
	Square Feet per Pallet	1,084.32 sq. ft (100.87 m <sup>2</sup> ) * 1202.8 sq. ft (111.89 m <sup>2</sup> )	
	Weight per Carton	42 lbs. (19 kg) *53 lbs (24 kg)	
	Weight per Pallet	2,060 lbs. (940 kg) *2120 lbs (960 kg)	
	Pallets per 20' Container	12	
	Pallets per 40' Container	24	